Saft Is17330, with 3 inch fly leads, 2/3 A 3.6V, 2100mah battery

Product price:

C\$20.33

Product short description:

The LS17330FL3 is a primary lithium- Cell Size Reference: 2/3 AA thionyl chloride battery of superior Part Number: LS17330FL3 quality, designed to energize your Nominal Capacity (mAh): 2100 3-inch flyleads for effortless Storage: + 30°C (+ 86°F) max incorporation. It boasts a high energy Diameter (Max): 16.5 mm (0.65 in) density, providing an extended service Height (Max): 33.4 mm (1.31 in) life and prolonged operational time. The Typical Weight: 14.4g (0.5 oz) construction features battery's hermetic glass-to-metal sealing and a 76°F/+ 185°F) non-flammable safety and dependability. As it adheres EAN / GTIN: 8438493107609 to safety standards and UL Component Termination Suffix: FL3 Recognition, fulfills requirements. The battery's operating temperature range, With a low self-discharge rate, the Compliancy: IEC 60086-4, IEC 60079-11 battery can maintain its power even Type of Termination: 3 Inch Fly Leads size bobbin cell offers a nominal Maximum Continuous Current: 25 capacity of 2.1 Ah and a pulse Nominal Energy: 7.56 Wh capability of up to 120 mA. It is perfectly suited for diverse applications such as utility metering, alarms, tracking The systems, among others. LS17330FL3, being compact and lightweight, can be easily incorporated into compact systems. Opt for the LS17330FL3 for high-performance applications that require reliability and durability.

Product features:

devices. This 3.6V battery is integrated Nominal Voltage: (at 0.2 mA + 20°C) 3.6V

a Operating Temperature Range: - 60°C/+ 85°C (-

electrolyte, ensuring Li Metal Content: approx. 0.6 g

stringent Warnings: Fire, explosion and burn hazard. Do not

wide solder directly to the cell

from Open Circuit Voltage: (at +20°C) 3.67V

-60°C to 85°C, guarantees efficient Storage Info: The storage area should be clean, cool performance even in harsh conditions. (preferably not exceeding + 30°C), dry and Ventilated

after being stored for a year. The 2/3 A- Pulse Capacity: Typically up to 120 mA

Product codes:

Reference: LS17330FL3 EAN13: 8438493107609

UPC: -

Product attributes:

Product gallery:







