

---

# Saft LS17330, LS-17330 Lithium Battery, 2/3 A 3.6V, 2100mAh

**Product price:**

**C\$16.89**

**Product short description:**

Presenting the LS17330, a primary lithium battery engineered to provide remarkable energy for your high-end applications. This 2/3 A-size bobbin cell delivers a trustworthy power solution due to its hermetic glass-to-metal sealing and non-combustible electrolyte. It boasts a consistent high voltage response and an extensive operating temperature range, spanning from -60°C to 85°C, making it an ideal choice for utility metering, tracking systems, alarms, automotive electronics, and other applications. In line with safety regulations and unrestricted for transport, this battery ensures both safety and ease of use. Its nominal capacity is 2.1 Ah and its nominal voltage is 3.6 V, guaranteeing durable performance. Opt for the LS17330 for superior energy density, dependability, and safety.

**Product features:**

Cell Size Reference: 2/3 AA  
Part Number: LS17330BA  
Nominal Capacity (mAh): 2100  
Nominal Voltage: (at 0.2 mA + 20°C) 3.6V  
Storage: + 30°C (+ 86°F) max  
Diameter (Max): 16.5 mm (0.65 in)  
Height (Max): 33.4 mm (1.31 in)  
Typical Weight: 14.4g (0.5 oz)  
Operating Temperature Range: - 60°C/+ 85°C (- 76°F/+ 185°F)  
Li Metal Content: approx. 0.6 g  
EAN / GTIN: 8438493107609  
Termination Suffix: BA  
Warnings: Fire, explosion and burn hazard. Do not solder directly to the cell  
Open Circuit Voltage: (at +20°C) 3.67V  
Storage Info: The storage area should be clean, cool (preferably not exceeding + 30°C), dry and Ventilated  
Compliance: IEC 60086-4, IEC 60079-11  
Type of Termination: Bare Cell  
Pulse Capacity: Typically up to 120 mA  
Maximum Continuous Current: 25  
Nominal Energy: 7.56 Wh

**Product codes:**

Reference: LS17330BA  
EAN13: 8438493107609  
UPC: -

**Product attributes:**

**Product gallery:**

---

