Saft LS17330 2/3 A 3.6V 2100mAh Lithium Battery with PC Pins - Single Positive & Dual **Negative Terminals**

Product price:

C\$19.15

Product short description:

The LS173303PFR Saft equipped with PC Pins, is a perfect fit Part Number: LS173303PFR for compact systems. This 2/3 A-size Nominal Capacity (mAh): 2100 and maintains a consistent voltage Storage: + 30°C (+ 86°F) max throughout its life cycle. Capable of Diameter (Max): 16.5 mm (0.65 in) operating within a temperature range of Height (Max): 33.4 mm (1.31 in) -60°C to 85°C and exhibiting a minimal Typical Weight: 14.4g (0.5 oz) self-discharge thrives rate. conditions. exceptionally harsh hermetically sealed structure and non- Li Metal Content: approx. 0.6 g combustible electrolyte enhance safety EAN / GTIN: 8438493107609 dependability. Meeting regulations, it's compatible with utility Warnings: Fire, explosion and burn hazard. Do not metering. alarms, electronics. and many applications. With a rated capacity of Storage Info: The storage area should be clean, cool this robust battery provides effective Compliancy: IEC 60086-4, IEC 60079-11 performance. Count on the system.

Product features:

battery, Cell Size Reference: 2/3 AA

bobbin cell boasts high energy density Nominal Voltage: (at 0.2 mA + 20°C) 3.6V

in Operating Temperature Range: - 60°C/+ 85°C (-

Its 76°F/+ 185°F)

safety Termination Suffix: 3PFR

automotive solder directly to the cell

other Open Circuit Voltage: (at +20°C) 3.67V

2.1 Ah and a nominal voltage of 3.6 V, (preferably not exceeding + 30°C), dry and Ventilated

Saft Type of Termination: With PC Pins (1 Pin on Positive

LS173303PFR for effortless installation Terminal & 2 Pin on Negative Terminal) and enduring power for your compact Pulse Capacity: Typically up to 120 mA

Maximum Continuous Current: 25

Nominal Energy: 7.56 Wh

Product codes:

Reference: LS173303PFR EAN13: 8438493107609

UPC: -

Product attributes:	Product gallery:	
	A STATE OF THE PARTY OF THE PAR	