# Opposite Tabs 2/3 A 3.6V 2100mAh Saft LS17330 Battery

## **Product price:**

C\$19.15

### **Product short description:**

Presenting the Saft LS17330CNR, a Cell Size Reference: 2/3 AA dependable and robust primary lithium- Part Number: LS17330CNR thionyl chloride battery suitable for a Nominal Capacity (mAh): 2100 size boasts a high energy density and Storage: + 30°C (+ 86°F) max guarantees a consistent, high voltage Diameter (Max): 16.5 mm (0.65 in) output throughout the life span of your Height (Max): 33.4 mm (1.31 in) device. The inclusion of tabs, fitted by Typical Weight: 14.4g (0.5 oz) our ISO-accredited workshop, simplifies Operating Temperature Range: - 60°C/+ 85°C (incorporation into compact systems. 76°F/+ 185°F) Complying with safety standards, the Li Metal Content: approx. 0.6 g hermetically and sealed combustible design provides assurance Termination Suffix: CNR an temperature range of -60°C to 85°C, solder directly to the cell this battery performs optimally even Open Circuit Voltage: (at +20°C) 3.67V suggested continuous current of 25 mA Compliancy: IEC 60086-4, IEC 60079-11 makes it an ideal choice for utilities Type of Termination: With Tabs (Opposite Directions) such as metering, alarms, automotive Pulse Capacity: Typically up to 120 mA electronics, among others. Choose Saft Maximum Continuous Current: 25 LS17330CNR for trustworthy power Nominal Energy: 7.56 Wh supply.

## **Product features:**

myriad of uses. This bobbin cell of 2/3 A- Nominal Voltage: (at 0.2 mA + 20°C) 3.6V

non- EAN / GTIN: 8438493107609

operational Warnings: Fire, explosion and burn hazard. Do not

under severe conditions. Its low self- Storage Info: The storage area should be clean, cool discharge rate coupled with a maximum (preferably not exceeding + 30°C), dry and Ventilated

#### **Product codes:**

Reference: LS17330CNR EAN13: 8438493107609

UPC: -

**Product attributes:** 

**Product gallery:** 

