
Saft LS26500 3.6V C-Size Battery with 3" Fly Leads, 3600mAh

Product price:

C\$45.19

Product short description:

Presenting the LS26500FL3, the optimal choice for high-energy density requirements! This battery is notable for its broad operating temperature spectrum and exceptional corrosion resistance, ensuring consistent performance over its lifespan. It is ideal for use in utility metering, buoys, industrial applications, and more, and features pre-installed 3-inch flyleads for straightforward integration. Boasting a nominal capacity of 7.7 Ah and a pulse capability of up to 300 mA, it provides dependable power in even the most challenging conditions. The LS26500FL3 meets safety standards, exhibits a low magnetic signature, and falls under restricted transportation classification. Its compact and lightweight design prioritizes ease of use. Opt for the LS26500FL3 for unparalleled performance and dependability.

Product features:

Cell Size Reference: C
Part Number: LS26500FL3
Nominal Capacity (mAh): 7700
Nominal Voltage: (at 0.2 mA + 20°C) 3.6V
Storage: + 30°C (+ 86°F) max
Diameter (Max): 26 mm (1.02 in)
Height (Max): 50.4 mm (1.98 in)
Typical Weight: 48g (1.7 oz)
Operating Temperature Range: - 60°C/+ 85°C (- 76°F/+ 185°F)
Li Metal Content: approx. 2.0 g
EAN / GTIN: 4250889624989
Termination Suffix: FL3
Warnings: Fire, explosion and burn hazard. Do not solder directly to the cell
Open Circuit Voltage: (at +20°C) 3.67V
Storage Info: The storage area should be clean, cool (preferably not exceeding + 30°C), dry and Ventilated
Compliance: IEC 60086-4, IEC 60079-11
Type of Termination: 3 Inch Fly Leads
Pulse Capacity: Typically up to 300 mA
Maximum Continuous Current: 150
Nominal Energy: 27.72 Wh

Product codes:

Reference: LS26500FL3
EAN13: 4250889624989
UPC: -

Product attributes:

Product gallery:

