

---

# C Size 3.6V 7700mah Saft LS26500 Battery with Parallel Tabs

**Product price:**

**C\$32.99**

**Product short description:**

Presenting the Saft LS26500CN primary lithium battery, now enhanced with tabs aligned in the same direction on both positive and negative terminals. Our authorized workshop guarantees precise installation, making assembly and connection more straightforward. This battery delivers dependable power due to its steady high voltage response, extensive temperature range (-60°C to 85°C), and minimal self-discharge rate. Contained within a stainless steel casing with a hermetic seal, it fulfills safety requirements and is resistant to corrosion. Ideal for uses such as utility metering, buoys, and measuring equipment, the LS26500CN boasts a nominal capacity of 7.7 Ah, a nominal voltage of 3.6V, and a pulse capability of 300 mA. Rely on Saft for exceptional performance and the option of low magnetic version availability.

**Product features:**

Cell Size Reference: C  
Part Number: LS26500CN  
Nominal Capacity (mAh): 7700  
Nominal Voltage: (at 0.2 mA + 20°C) 3.6V  
Storage: + 30°C (+ 86°F) max  
Diameter (Max): 26 mm (1.02 in)  
Height (Max): 50.4 mm (1.98 in)  
Typical Weight: 48g (1.7 oz)  
Operating Temperature Range: - 60°C/+ 85°C (- 76°F/+ 185°F)  
Li Metal Content: approx. 2.0 g  
EAN / GTIN: 4250889624989  
Termination Suffix: CN  
Warnings: Fire, explosion and burn hazard. Do not solder directly to the cell  
Open Circuit Voltage: (at +20°C) 3.67V  
Storage Info: The storage area should be clean, cool (preferably not exceeding + 30°C), dry and Ventilated  
Compliance: IEC 60086-4, IEC 60079-11  
Type of Termination: With Tabs (Same Direction)  
Pulse Capacity: Typically up to 300 mA  
Maximum Continuous Current: 150  
Nominal Energy: 27.72 Wh

**Product codes:**

Reference: LS26500CN  
EAN13: 4250889624989  
UPC: -

**Product attributes:**

**Product gallery:**

---

