Saft LSH20 3.6V D Size Lithium Battery 3.6V -Non Rechargeable

Product price:

C\$65.53

Product short description:

Introducing the Saft 3.6V LSH20 Cell Size Reference: D Lithium Battery, a high-powered, non- Part Number: LSH20BA rechargeable battery designed for Nominal Capacity (mAh): 13000 features a substantial capacity of Storage: + 30°C (+ 86°F) max 13,000Mah and an incredibly high Diameter (Max): 33.4 mm (1.32 in) that voltage response consistent throughout most of its Typical Weight: 100g (3.5 oz) lifespan.

This battery is not for use as a Li Metal Content: approx. 3.8 g replacement for standard 1.2V or 1.5V EAN / GTIN: 4016138771732 D batteries, but rather for specialist Termination Suffix: BA - the Bare Cell and the Saft LSH20 D solder directly to the cell lithium with Tabs.

The Saft LSH20 is renowned exceptional reliability. This powerhouse Type of Termination: Bare Cell operates using Thionyl Chloride, offering a super low Maximum Continuous Current: 1800 discharge and up to a 10-year shelf life. Nominal Energy: 46.8Wh It comes encased in a stainless steel container with end caps, ensuring a minimal magnetic signature.

For added safety, it features a nonflammable electrolyte and uses hermetic glass for metal sealing, providing exceptional reliability. This battery can operate in а wide temperature range of -60°C to 85°C, and it is not restricted for transport as

Product features:

specialized applications. This battery Nominal Voltage: (at 2 mA + 20°C) 3.6 V remains Height (Max): 61.6 mm (2.42 in) Operating Temperature Range: - 60°C/+ 85°C (-76°F/+ 185°F) applications. It is available in two types Warnings: Fire, explosion and burn hazard. Do not Open Circuit Voltage: (at +20°C) 3.67V Storage Info: The storage area should be clean, cool in (preferably not exceeding + 30°C), dry and Ventilated industrial and military fields for its Compliancy: IEC 60086-4, IEC 60079-11 advanced Lithium Pulse Capacity: Typically up to 4000 mA

per the UN Recommendations on the transport of dangerous goods – Model Regulations.

Key Features:

- D Size
- 13,000Mah Capacity
- Lithium Thionyl Chloride (Li-SOCI2)
- Chemistry
- 3.6V Voltage
- Length: 61.70 mm
- Diameter: 32 mm

Other Specifications:

- Cell type construction: D
- Open Circuit Voltage: 3.67 V
- Nominal Voltage: 3.6 V
- Nominal capacity (drain): 13.0 Ah (15 mA)
- Max. recommended Continuous Current: 1.8 A
- Operating temp. range: -60/ 85°C
- Outside diameter max: 33.4 mm
- Length max: 61.6 mm
- Weight: 100 g
- Transport: Restricted (Class 9)

Compatible with numerous battery part numbers, the Saft LSH20 is perfect for specialized applications that require a 3.6V D battery. Add as many batteries as you need to your cart, and avail of our amazing deals and discounts for bulk orders. Please note that for orders exceeding the displayed quantity, further discounts may be available upon contacting us.

Product codes:

Reference: LSH20BA EAN13: 4016138771732 UPC: -

Product attributes:





