
Battery for Lumicron4013, Dv-5, Ee-pack-33, Ldc-4013, Ldc-4230, 3.7V, 1050mAh - 3.89Wh

Product price:

C\$25.75

Product short description:

High quality Battery for Lumicron4013, Dv-5, Ee-pack-33, Ldc-4013, Ldc-4230, 3.7V, 1050mAh - 3.89Wh Our products are shipped from Canada using fast reliable carriers including Canada Post, UPS, Purolator & FedEx. Check out our detailed product description for more information with regards to this product

Product features:

Dimensions (mm): 53.20 x 35.30 x 7.10mm
Capacity.: 1050mAh
Chemistry.: Li-ion
Length (inches).: 2.09
Width (inches).: 1.39
Height (inches).: 0.28
Length (mm).: 53.2
Height (mm).: 7.1
Width (mm).: 35.3
Voltage.: 3.7V
Gross Weight.: 0.048 Kg
Colour.: Black
Ean Code: 4894128005261
Net Weight.: 0.0234 Kg
Our Part Number: CS-NP60FU
Watt Hour.: 3.885Wh
Description: Canadian Batteries supplies high quality, Batteries For Lumicron4013, Dv-5, Ee-pack-33, Ldc-4013, Ldc-4230, 3.7v, 1050mah - 3.89wh
Warranty Period: 30 Days to return for refund & 1 Year replacement warranty on this product.

Product codes:

Reference: CS-NP60FU
EAN13: 4894128005261
UPC: -

Product attributes:

Product gallery:



Sony **LI-ION BATTERY PACK**
Model: NP-FW50
Capacity: 1500mAh (nominal)
Voltage: 3.7V (nominal)
Dimensions: 34.5 x 26.5 x 14.5 mm

SAFETY PRECAUTIONS:

- DO NOT EXPOSE TO HIGH TEMPERATURES, OPEN FLAME OR FIRE.
- DO NOT DISASSEMBLE, OPEN OR SERVICE THE BATTERY PACK.
- DO NOT SHORT CIRCUIT THE BATTERY PACK TERMINALS.
- DO NOT CRUSH, PUNCTURE, BEND OR DEFORM.
- CONTACTS ON SURFACE OF BATTERY PACK MUST NOT BE TOUCHED.

WARRANTY: Sony warrants this battery pack for a limited period of time against defects in materials and workmanship under normal use and conditions.

RECYCLING: This battery pack is made of recyclable materials. Please dispose of it properly.

REGULATORY COMPLIANCE: CE, FCC, RoHS, WEEE, REACH, PSE, UN38.3, IEC 60086-0, IEC 60950-1, IEC 60950-2, IEC 60950-3, IEC 60950-4, IEC 60950-5, IEC 60950-6, IEC 60950-7, IEC 60950-8, IEC 60950-9, IEC 60950-10, IEC 60950-11, IEC 60950-12, IEC 60950-13, IEC 60950-14, IEC 60950-15, IEC 60950-16, IEC 60950-17, IEC 60950-18, IEC 60950-19, IEC 60950-20, IEC 60950-21, IEC 60950-22, IEC 60950-23, IEC 60950-24, IEC 60950-25, IEC 60950-26, IEC 60950-27, IEC 60950-28, IEC 60950-29, IEC 60950-30, IEC 60950-31, IEC 60950-32, IEC 60950-33, IEC 60950-34, IEC 60950-35, IEC 60950-36, IEC 60950-37, IEC 60950-38, IEC 60950-39, IEC 60950-40, IEC 60950-41, IEC 60950-42, IEC 60950-43, IEC 60950-44, IEC 60950-45, IEC 60950-46, IEC 60950-47, IEC 60950-48, IEC 60950-49, IEC 60950-50, IEC 60950-51, IEC 60950-52, IEC 60950-53, IEC 60950-54, IEC 60950-55, IEC 60950-56, IEC 60950-57, IEC 60950-58, IEC 60950-59, IEC 60950-60, IEC 60950-61, IEC 60950-62, IEC 60950-63, IEC 60950-64, IEC 60950-65, IEC 60950-66, IEC 60950-67, IEC 60950-68, IEC 60950-69, IEC 60950-70, IEC 60950-71, IEC 60950-72, IEC 60950-73, IEC 60950-74, IEC 60950-75, IEC 60950-76, IEC 60950-77, IEC 60950-78, IEC 60950-79, IEC 60950-80, IEC 60950-81, IEC 60950-82, IEC 60950-83, IEC 60950-84, IEC 60950-85, IEC 60950-86, IEC 60950-87, IEC 60950-88, IEC 60950-89, IEC 60950-90, IEC 60950-91, IEC 60950-92, IEC 60950-93, IEC 60950-94, IEC 60950-95, IEC 60950-96, IEC 60950-97, IEC 60950-98, IEC 60950-99, IEC 60950-100.